



Panalog To Cineon		
Panalog	Linear	Cineon

64	0.00000	95
88	0.00567	119
97	0.00798	129
109	0.01124	144
125	0.01591	164
146	0.02266	193
171	0.03172	235
202	0.04470	280
239	0.06320	325
282	0.08966	370
330	0.12708	416
382	0.17963	461
437	0.25300	505
496	0.35883	551
557	0.50820	596
619	0.71704	641
683	1.01598	687
748	1.44019	732
812	2.02363	776
878	2.86661	822
936	3.88709	861
1011	5.75453	913
1019	6.00000	918

Linear Light%	Waveform%	Exposure Stops Rel. 18%
---------------	-----------	-------------------------------

0.0	0	Black
0.6	3	-5
0.8	4	-4.5
1.1	5	-4
1.6	7	-3.5
2.3	9	-3
3.2	12	-2.5
4.5	16	-2
6.3	20	-1.5
9.0	25	-1
12.7	30	-0.5
18.0	36	0
25.3	43	0.5
35.9	49	1
50.8	56	1.5
71.7	63	2
101.6	71	2.5
144.0	78	3
202.4	85	3.5
286.7	93	4
388.7	100	4.5
575.5	108	5
600.0	109	MAX



## Genesis Exposure Chart

### E.I. 400

Linear Light % Reflectance	Waveform%	Exposure Stops Rel. 18%
600.0	109	MAX
575.5	108	5
388.7	100	4.5
286.7	93	4
202.4	85	3.5
144.0	78	3
101.6	71	2.5
71.7	63	2
50.8	56	1.5
35.9	49	1
25.3	43	0.5
18.0	36	0
12.7	30	-0.5
9.0	25	-1
6.3	20	-1.5
4.5	16	-2
3.2	12	-2.5
2.3	9	-3
1.6	7	-3.5
1.1	5	-4
0.8	4	-4.5
0.6	3	-5
0.0	0	Black